

Ethernet APL

Advanced Physical Layer





A look back – the origins of Ethernet APL

Ethernet APL Group



Core objectives:



Protocol independent



Simple and robust connections



Modern technology and simple commissioning



Higher data speed

































What is Ethernet? What is Ethernet APL?

What is Ethernet APL?

Overview



- Advanced Physical Layer (Ethernet in the sensor)
- 2-wire technology (supply + communication)
- Data bandwidth up to 10 Mbit/s
 - ~10,000 times faster than HART!
- Up to 1000 m cable length



Data transmission in kbit/s

What is Ethernet APL?

Overview





Intrinsically safe supply Ex ia

Protocols:










- PROFINET, Modbus TCP/IP, OPC-UA, Web-Server
- Ethernet/IP, Modbus TCP/IP, OPC-UA, Web-Server

Option to implement security in accordance with IEC 62443-4-2

How is an Ethernet APL network structured?


Ethernet APL

Ex concept: Compact systems



Ethernet APL

Ex concept: Extensive systems



Comparison with today's technologies

	4 20 mA/HART	PROFID® FOUNDATION Profibus PA & Foundation Fieldbus	⊘ IO -Link IO-Link	EtherNet/IP	PC FOUNDATION OPC/UA
Level	Field	Field	Machine	PLC, Field	PLC, Field
Benefits	Automation	Automation	Automation	Automation	IIoT, Visualisation
Cable	Two-wire	Two-wire	Three-wire	Two-wire	Two-wire
Connection, Ex i	Terminals 🗽	Terminals, SUB-D	M12	Terminals 🗽	Terminals (Ex)
Range	1000 m	1000 m	20 m	1000 m	1000 m
Topology	Point-to-point	Line, tree, star, ring	Point-to-point	Point-to-point	Point-to-point
Speed	Very slow	Slow	Fast	Very fast	Very fast
VEGA products	Continuous sensors/devices	Continuous sensors	New sensors BASIC	Future sensors & devices with Ethernet	Future sensors & devices with Ethernet
Industry	Process automation	Process automation	Factory automation	Process automation	Visualisation and diagnosis

What is the performance of Ethernet APL?

Performance

Specifications VEGAPULS 6X 80-GHz Ethernet APL

	VEGAPULS 6X Ethernet-APL	VEGAPULS 6X 4 20 mA/HART
Transmission rate	APL: 10 Mbit/s = 10 000 kbit/s	HART: 1.2 kbit/s
Sampling rate	10 measurements/s	4 measurements/s
Operation	Standard operation: - DTM via serial interface - PLICSCOM - App via Bluetooth High-performance operation: - FDI package - DTM via network - Web server	Standard operation: - DTM via serial interface - PLICSCOM - App via Bluetooth - FDI package

What adjustment options are available?

Web browser



Web browser









